

Table of Contents

- UCH Wiki Syntax TABLES** 3
- Basic Syntax** 3
- No-Header** 3
- Complex Headers** 3
- Options** 4
 - Extra Options 5
- Extensions** 5

UCH Wiki Syntax TABLES

Basic Syntax

```
<datatables>
^ Column A ^ Column B ^ Column C ^
| Row A1 | Row B1 | Row C1 |
| Row A2 | Row B2 | Row C2 |
| Row A2 | Row B2 | Row C3 |
</datatables>
```

Column A	Column B	Column C
Row A1	Row B1	Row C1
Row A2	Row B2	Row C2
Row A2	Row B2	Row C3

No-Header

```
<datatables>
<datatables header-rows="true">
| Row A1 | Row B1 | Row C1 |
| Row A2 | Row B2 | Row C2 |
| Row A2 | Row B2 | Row C3 |
</datatables>
</datatables>
```

Row A1	Row B1	Row C1
Row A2	Row B2	Row C2
Row A2	Row B2	Row C3

Complex Headers

```
<datatables>
^ Name ^^
```

```

^ First ^ Last ^
| My | Name |
| Your | Name |
</datatables>
    
```

Name	
First	Last
My	Name
Your	Name

Options

Option	Description	Allowed values	Default value
scroll-y	Vertical scrolling	px, integer, boolean	false
scroll-x	Horizontal scrolling	px, integer, boolean	false
page-length	Number of elements to display per page	integer	10
paging	Enable or disable table pagination	boolean	true
ordering	Feature control ordering (sorting) abilities in DataTables	boolean	true
info	Feature control table information display field	boolean	true
order	Initial order (sort) to apply to the table	json	[[0, 'asc']]
searching	Feature control search (filtering) abilities	boolean	true
length-change	Feature control the end user's ability to change the paging display length of the table	boolean	true
state-save	State saving - restore table state on page reload	boolean	false
auto-width	Feature control DataTables' smart column width handling	boolean	true
paging-type	Pagination button display options	simple - 'Previous' and 'Next' buttons only simple_numbers - 'Previous' and 'Next' buttons, plus page numbers full - 'First', 'Previous', 'Next' and 'Last' buttons full_numbers - 'First', 'Previous', 'Next' and 'Last' buttons, plus page numbers	simple_numbers

Option	Description	Allowed values	Default value
dom	Define the table control elements to appear on the page and in what order	string	lfrtip

Notes

* The option names are actually used as HTML5 data attributes, so they must be formatted with hyphens-and-lower-case instead of camelCase (see <https://datatables.net/manual/options#HTML-5-data-attributes>). * Do not prepend option names with data-. The prefix will be added by the plugin. * Complex option values must be specified using valid JSON, wrapped with single quotes '. For example: order=' [[0, "asc"]]' or search=' {"search": "fred"}'.

Extra Options

The plugin also implements extra features beyond the options from DataTables jQuery library.

Option	Description	Allowed values	Default value
header-rows	Makes sure the table header contains at least the specified number of rows, so that it can be formatted by DataTables. It transfers the first rows of the table body into the table header if necessary. Particularly useful when formatting tables generated by other plugins, which may not have created a proper table header.	integer	0 (no effect)

Extensions

	Attribute	Example
Fixed Header	fixed-header	fixed-header="true" or fixed-header='{ "header": true, "headerOffset": 50 }'
Fixed Columns	fixed-columns	fixed-columns="true"
Responsive	responsive	responsive="true"
Buttons	buttons	buttons=' ["copy", "csv", "print"]'

Taken from [UCH Wiki](#).

From: <https://wiki.ulascemh.com/> - **UCH**

Permanent link: <https://wiki.ulascemh.com/doku.php?id=syntax:tables:start>

Last update: **2026/04/12 12:07**



